

## NIBP, SpO2 & ECG Monitor



8.4" color TFT

### TECHNICAL SPECIFICATION

ECG		SpO <sub>2</sub>	
Lead Mode	5 Leads (RA, LA, LL, RL, V)	Measuring Range	0 ~ 100 %
Lead Selection	I, II, III, avR, avL, avF, V	Resolution	1 %
Lead Mode	3 Leads (RA, LA, LL,)	Accuracy	70% ~ 100% ± 2%
Lead Selection	I, II, III	<b>Pulse Rate</b>	
Gain	x2.5mm/mV, x5.0mm/mV, 10mm/mV, x20mm/mV	Measuring Range	0-254bpm
<b>HR Range</b>		Resolution	1 bpm
Adult	15 ~ 300 bpm	Accuracy	± 2bpm
Neo/Ped	15 ~ 350 bpm	<b>Recorder</b>	Optional
Accuracy	± 1 bpm	<b>Standard</b>	
Resolution	1 bpm	<b>Accessories</b>	ECG Patient Cable 1 No.
Sensitivity	> 200 uV P-P		SpO2 Adult Sensor Probe 1 No.
			NIBP Cuff 1 No.
			Power Cord 1 No.
<b>NIBP</b>		<b>Power</b>	
Method	Oscillometric	Power Supply	100 / 250 VAC, 50 / 60 Hz
Mode	Manual, Auto, STAT	<b>Size &amp; Weight</b>	
Parameters	SYS, DIA, MEAN	Monitor Size	318 x 152 x 264 mm
Repeat Cycles	1-5, 10, 15, 30, 60, 90, 120, 180, 240, 480 Min	Monitor Weight	5.5 kg (Appr.)
<b>Measuring Range</b>			
Adult	10 ~ 270 mmHg		
Pediatric	10 ~ 200 mmHg		
Neonate	10 ~ 135 mmHg		
Resolution Pressure	1 mmHg		

\* Due to continues upgradation features subject to change without prior notice.