

SpO2 & NIBP Monitor

Features:

- **Compact** and **portable**, uninterrupted monitoring with built-in battery
- High bright **LED** display of **SPO2, NIBP** and **PULSE RATE**
- High resolution color **LCD** for trend tabular and SPO2 waveforms display and LED for numeric display (SPO2/NIBP/PR)
- **Manual / Auto** measurement of NIBP
- Adjustable audible and visual alarms
- Up to **2000** NIBP data storage of **3000** SPO2 data
- Suitable for **adult, pediatric** and **neonatal** patients



Technical Specification:

Display:

- 7 segment LEDs for SPO2, NIBP and pulse rate
- 2.9" color LCD for waveforms, bargraphics, trend and system menu

NIBP:

- **Method:** Oscillometry
- **Operation mode:** Manual / Automatic
- **Auto Measure Time:** 1~255 minutes adjustable, interval 5 minutes
- **Measurement Range:** 40~270mmHg
- **Overpressure Protection:** Yes
- **Resolution:** 1mmHg
- **Alarm:** Systolic, Diastolic, Mean

SPO2:

- **Measurement range:** 35~99%
- **Resolution:** 1%
- **Alarm range:** 35~99%

Pulse Rate:

- **Range:** 30~250bpm
- **Resolution:** 1bpm
- **Accuracy:** ±1bpm

Dimension, Weight & Power Supply:

- **Dimension:** 232*198*75mm
- **Weight:** about 0.95kg
- **Power supply:** 7.4 V 2000 mAh

* Due to continues upgradation features subject to change without prior notice.



Exclusively Mkted. By:

ASPEN DIAGNOSTICS PVT. LTD.
Rapid Diagnostic Group of Companies
 (ISO 9001 : 2000 CERTIFIED COMPANY)

LOCAL CONTACT