



# URINE ANALYZER

## Uri-Plus 1A & 5A

- ACCURATE AND EFFICIENT
- EASY TO OPERATE
- CONVENIENT TO USE
- DATA MANAGEMENT CAPABILITY

### SPECIFICATIONS

Model	Uri-Plus 5A (Touch Screen)	Uri-Plus 1A (Key Pad)
Methodology	Reflectance Photometry	Reflectance Photometry
Detection	Photosensitive diode	Photosensitive diode
Throughput	500 tests/hour	120 tests/hour
Test modes	Routine STAT and QC	Routine /QC
Memory	Last 2000 records	Last 2000 records
Strip incubation time	1 minute	1 minute
Wavelength	525 and 635 nm	525 and 635 nm
Standard strips	2,4, 10, 11 parameter (5mmx110mm)	2,4, 10, 11 parameter (5mmx110mm)
Waste disposal capacity	Up to 150 strips	NA
PC port	Standard RS232C port	Standard RS232C port
Printer	Internal thermal printer	Internal thermal printer
Sockets	RS232C barcode reader port, 25 pin parallel external printer	RS232C barcode reader port, 25 pin parallel external printer
Calibration	Automatic	Automatic
Available languages on the screen	English & additional languages	English & additional languages
Operating conditions	0-40°C (32-104°F) 85%RH	0-40°C (32-104°F) 85%RH
Storage condition	0-40°C (32-104°F) 85%RH	0-40°C (32-104°F) 85%RH
Dimensions (LxWxH)	36.6cm x 28.3cm x 19.5 cm	36.6cm x 28.3cm x 19.5 cm
Display dimension (LxW)	11.8cm x 9.0cm	11.8cm x 9.0cm
Weight	4.0 kg	2.6 kg



Mkt. By:  
**RAPID DIAGNOSTIC PVT. LTD.**  
ISO 9001 : 2000 CERTIFIED COMPANY  
B-82, G.T.K Road Indl. Area, Delhi-110 033

Local Contact:



*Compact & Easy to Use*

www.rapidiagnostic.in